

QUATTRO IN-DUCT UV AIR PURIFIER

With mounting frame/handles

Ship. Dim. /weight (bulk)		
Dim.	Lamp Assembly	4.37" diameter x 24.375" length (111mm x 619mm)
	Ballast box	24" x 8" x 2.75" (610mm x 203mm x 70mm)
	Weight	20.5 lbs (9.3 Kg)
Electrical		
Option	Power	160W
	Voltage	120/240 VAC, 50/60 Hz
	Startup	Rocker ON/OFF switch on ballast box
	Dry contacts for BMS	Up to 4
Construction		
Option	Parabolic reflectors(4)	Extruded aluminum
	Lamp assembly	24" in length, adjustable posts to center the unit (5" extendable)
	Number of ballasts	4
	Cable	6 ft 3-prong computer type cord
	Harware supplied	Mounting frame and screws and nuts for the frame and the unit
	Safety	Integrated safety switch that shuts the unit off when removed from mounting frame
	BMS option	Requires infactory installation of electronic card
Lamps		
Lamps	Type	Quartz Tube 3/4 " (19mm) T6- 4 pins
	Number of lamps	4
	Lamp type	Straight lamp
	Lamp length	18" (457mm)
	UVC dosage	Sized according to HVAC parameters. Refer to calculations provided
Warranty		
Warranty	Ballasts	3 years
	Lamps	17 000 hrs or 2 yrs, first occurrence
	Electronic	3 years
Replacement parts		
Replacement parts	Ballast(s) (4)	BST120/277GL
	UVC Lamp(s) (4)	LMPHGS180 (Germicidal only, purple caps) - LMPHGXS180 (Odor control, yellow caps)

